



# Arcoated™ PVDF Plus

## Pre-painted galvanized steel for construction and general industry

<b>Applications</b>	General outdoor applications like cladding, roofing, constructions accessories.	
<b>Properties</b>	It is highly resistant to solar radiation and environments characterized by high levels of pollution.	
<b>Description</b>	Total paint thickness (Front side) Layered composition	25µm(EN 13523-1) Front: primer 5 µm +20 µm top coat Back: 7 µm Double side finish available
	Gloss	30 G.U.
	Colours	Colour palette. Other colours on request
	Appearance	Smooth
	Temporary film protection	On request
<b>Performance</b>	Mechanical properties	Standard quality : EN10346
	Size	Width max.1500 mm Thickness max 1,5 mm ;min 0,3 mm Tolerances EN 10143
	Impact test	18 J(EN 13523-5)
	Paint adherence (T-bend)	≤ 1t(EN 13523-7)
	Resistance to cracking on bending (T-bend)	≤ 1t(EN 13523-7)
	Surface pencil hardness	HB– H(EN 13523-4)
	Corrosion resistance:	
	• Salt spray test	500h(EN 13523-8)
	• Corrosion resistance category	RC3
	Condensation resistance	>1000h(EN 13523-26)
	UV resistance:	
	• QUV(UVA+H2O)test (2000h)	ΔE≤2; G.R. ≥80%
	• UV resistance category	RUV4
	Fire behaviour classification (DM 10-3-2005)	A1
	Environment	CrVI-free ; RoHS 2011/65/UE
<b>Guarantee</b>	Non-perforation of the sheet metal	≤ 21 years (*)
	Non-delamination of the paint	≤ 21 years (**)
	Aesthetic appearance (ΔE≤5; G.R. ≥50%)	≤ 12 years (**)
		(*) refer to document ARVEDI GUARANTEE on section transport, stocking, building (**) refer to document ARVEDI GUARANTEE on section geographical location and RUVn category.