

Environmental Product Declaration



In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:

Steel Structural circular, square and rectangular hollow sections

from

Arvedi Tubi Acciai Spa

Arvedi Tubi Acciaio

Programme:	The International EPD® System, www.environdec.com
Programme operator:	EPD International AB
EPD registration number:	S-P-06004
Publication date:	2022-05-31
Revision date:	2024-10-14
Valid until:	2027-05-24

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com



General information

Programme information

Programme:	The International EPD® System
Address:	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
Website:	www.environdec.com
E-mail:	info@environdec.com

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product category rules (PCR): *PCR CONSTRUCTION PRODUCTS, PCR 2019:14, VERSION 1.11*
CPC code: 41287 Other tubes and pipes, of circular cross-section, welded, of steel
41288 Tubes and pipes, of non-circular cross-section, welded, of steel

PCR review was conducted by:

PCR moderator: Martin Erlandsson, IVL Swedish Environmental Research Institute, martin.erlandsson@ivl.se

PCR Committee: IVL Swedish Environmental Research Institute

Secretariat of the International EPD® System

Independent third-party verification of the declaration and data, according to ISO 14025:2006:

☐ EPD process certification ☒ EPD verification

Third party verifier: *RINA Services S.p.A*

In case of accredited certification bodies:

Accredited by: *Accredia, n. 0002VV*

Procedure for follow-up of data during EPD validity involves third party verifier:

☒ Yes ☐ No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.

Company information

Owner of the EPD: Arvedi Tubi Acciaio S.p.A.

Contact: sales@ata.arvedi.it

Description of the organisation

Advanced technology, experience consolidated over the years, the constant search for quality, flexibility and customer service, are the strong points of Arvedi Tubi Acciaio S.p.A, a leader in welded tube for special applications.

With a production capacity of over 600,000 tpy, the Cremona-based company holds a considerable share of the market in the automotive, mechanical applications, heat transfer and pressure equipment, piping, industrial and civil constructions.

Its stretch-reducing mill and HFI welding lines, fitted with the most advanced automation technology, allow customer to be offered a vast range of products that can meet the strictest requirements and standards.

ATA's production range meets the requirements of three basic areas of application, namely special, energy and civil engineering and includes round tube and pipe in diameters from 17.2 to 355.6 mm. Square hollow section from 90x90 to 300x300 mm and rectangular hollow section from 100x80 to 400x200 mm in a range of wall thicknesses from 1,2 to 16 mm.

Product-related or management system-related certifications:

Arvedi Tubi Acciaio has a management system certified according to ISO 14001 (environment), ISO 50001 (energy), ISO 9001 & IATF 16949:2016 (quality) and ISO 45001 (health and safety).

Name and location of production site.

The production sites are in Cremona, Italy, Via Acquaviva, 3 & 6 (Zona Porto Canale).



Vista aerea dello stabilimento – Arvedi Tubi Acciaio (ATA)

Product information

Product name

- Steel structural circular hollow sections
- Steel structural square and rectangular hollow sections, cold finished and hot finished

Product identification and description

Product	Description	Sales markets
Steel structural circular hollow sections	Circular hollow section for structural uses in accordance with EN standards: EN10219-1; EN 10219-2; EN 10210-1; EN 10210-2	Europe
Steel structural square and rectangular hollow sections	Square and rectangular hollow section in accordance with EN standards: EN10219-1; EN 10219-2; EN 10210-1; EN 10210-2	Europe

ARVEDI Hollow sections are also produced according to other international standards and steel grades EN / ASTM / CSA.

ARVEDI hollow sections produced on the base of EN10219-1 & EN10210-1 are covered by CE mark in accordance with Regulation (EU) No. 305/2011; the material certificate and the declaration of performance accompany each supply.

ARVEDI structural circular hollow sections produced on EN10210-1 are DNV GL approved according DNV GL rules for classification – ships & offshore standards.

UN CPC code

- 41287 Other tubes and pipes, of circular cross-section, welded, of steel
- 41288 Tubes and pipes, of non-circular cross-section, welded, of steel

LCA information

Functional unit:

The functional unit is 1 ton of product (structural tubes)

Time representativeness

The reference year of the LCA study is 2023

Database and LCA software used

Ecoinvent 3.10 allocation, cut-off by classification, March 2024; Sima Pro 9.6

The reference package used for impact indicator is based on EF 3.1.

Description of system boundaries

The system boundaries are: Cradle to gate with options: modules A1-A3 + module A4 + C + D

System diagram



More information

The specific mix of supply coils was also considered for each product (BOF or EAF).

Energy consumption and emissions are specific to each production line and for each product the percentage of production on the various lines has been considered.

For the electricity used in the plant it's used the Italian residual mix according to Ecoinvent 3.10.

With regard to transport to the customer, the information required by EN 15804 is explained:

Parameter	Unit	Value			
Means used	n.a.	articulated lorry, euro 5 + ship			
Distance to customer	km	Product	lorry	ship	train
		tubes	362	12	308
		square and rectangular hollow sections	579	24	401

It is the weighted average distance, considering all the sales markets.

Percentage of use	%	97% of transport was optimized for weight
Density of the transported product	g/ml	Variable according to the section

End of life scenario

The end of life was modelled on the basis of the end of life data of the construction products of the states that contribute at least 5% to the sales of the two products. They have all been located within the EU.

Module C1: the consumption of diesel for demolition operations was assumed from “Waste bulk iron process, excluding reinforcement {RER} | treatment of, sorting plant”

Module C2: a transport distance to a treatment centre of 50 km was assumed

Module C3: a recycling rate of 90% for tubes and 89% for square hollows was used, deriving from the average recycling percentage weighed on the sales of the various countries - Eurostat data for demolition waste in Europe in 2020.

Module C4: a landfill rate of 10% for tubes and 11% for square hollows was assumed, a percentage indicated by Eurostat for demolition waste in Europe, calculated as in the previous point.

Module D: the advantage is considered as the difference between the impacts of a blast furnace, in which virgin minerals are used, and a second smelting steel plant.

In the calculation of the environmental advantage, the melting yield is considered and the content of recycled material already present in the purchased coils is separated, as per module D of EN 15804.

Modules declared, geographical scope, share of specific data (in GWP-GHG indicator) and data_variation

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X
Geography	RoW	EU	IT	RoW									EU	EU	EU	EU	
Specific data used	21% for tubes 19% for square sections					-	-	-	-	-	-	-	-	-	-	-	-
Variation – products	-23% / +4% for tubes -32% / +10% for square sections					-	-	-	-	-	-	-	-	-	-	-	-
Variation – sites	n.a.					-	-	-	-	-	-	-	-	-	-	-	-

According to the PCR only the specific data from EPD of suppliers, natural gas consumption of the plant and the transport of incoming semi-finished products were considered specific data. The data from Ecoinvent database are not considered specific data.

Content information

Steel structural circular hollow sections

Product components	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%
Carbon steel	1000	38% *	0%
TOTAL	1000		
Packaging materials	Weight, kg	Weight-% (versus the product)	
Straps, seals and steel wire rods	2,8	0,3%	
Polyester bands	0,3	0,03%	
TOTAL	3,1		

* the data comes from the suppliers' recycled content certificates

Steel structural square and rectangular hollow sections

Product components	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%
Carbon steel	1000	27%*	0%
TOTAL	1000		
Packaging materials	Weight, kg	Weight-% (versus the product)	
Straps, seals and steel wire rods	2,3	0,2%	
Polyester bands	0,2	0,02%	
TOTAL	2,5		

* the data comes from the suppliers' recycled content certificates.

The products don't contain dangerous substances from the candidate list of SVHC for Authorisation in quantity greater than 0,1%.

Environmental Information

Potential environmental impact – mandatory indicators according to EN 15804

Steel structural circular hollow sections

Results per functional or declared unit (1 t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
GWP-fossil	kg CO ₂ eq.	1,53E+03	3,08E+01	2,42E+01	1,58E+03	6,03E+01	4,31E+00	5,36E+00	2,38E+01	5,63E-01	-2,78E+02
GWP-biogenic	kg CO ₂ eq.	1,71E+00	2,22E-02	1,13E-01	1,84E+00	9,11E-02	3,11E-02	2,77E-03	-3,08E-01	7,76E-05	2,52E+00
GWP-luluc	kg CO ₂ eq.	1,67E+00	1,80E-02	2,46E-02	1,71E+00	2,88E-02	3,88E-03	1,84E-03	3,36E-02	2,90E-04	5,85E-02
GWP-total	kg CO ₂ eq.	1,53E+03	3,09E+01	2,44E+01	1,59E+03	6,04E+01	4,35E+00	5,37E+00	2,35E+01	5,63E-01	-2,76E+02
ODP	kg CFC 11 eq.	1,37E-05	4,71E-07	4,66E-06	1,88E-05	1,16E-06	8,20E-08	1,08E-07	3,27E-07	1,63E-08	-4,57E-07
AP	mol H ⁺ eq.	7,04E+00	6,97E-01	6,90E-02	7,80E+00	2,36E-01	2,23E-02	1,73E-02	2,61E-01	3,99E-03	-8,17E-01
EP-freshwater	kg P eq.	4,80E-01	2,19E-03	5,46E-03	4,88E-01	6,27E-03	1,05E-03	3,65E-04	1,36E-02	4,67E-05	-1,20E-01
EP-marine	kg N eq.	1,64E+00	1,78E-01	2,03E-02	1,84E+00	8,22E-02	7,73E-03	5,88E-03	6,07E-02	1,52E-03	-2,10E-01
EP-terrestrial	mol N eq.	1,69E+01	1,98E+00	1,77E-01	1,90E+01	8,92E-01	8,28E-02	6,40E-02	6,82E-01	1,66E-02	-2,30E+00
POCP	kg NMVOC eq.	5,90E+00	5,48E-01	6,76E-02	6,52E+00	3,52E-01	2,83E-02	2,82E-02	2,04E-01	5,94E-03	-8,35E-01
ADP-minerals & metals *	kg Sb eq.	2,66E-03	4,56E-05	1,36E-04	2,84E-03	1,65E-04	2,10E-05	1,45E-05	1,46E-03	8,79E-07	3,39E-04
ADP-fossil*	MJ	1,63E+04	3,97E+02	2,24E+02	1,69E+04	8,73E+02	6,80E+01	7,77E+01	3,21E+02	1,38E+01	-2,32E+03
WDP	m ³	4,53E+02	1,50E+00	3,65E+00	4,58E+02	4,84E+00	4,77E-01	3,70E-01	3,98E+00	6,03E-01	-2,14E+01
Acronyms	GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption										

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

The negative value in module D indicates an environmental benefit.

Steel structural square and rectangular hollow sections

Results per functional or declared unit (1 t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
GWP-fossil	kg CO ₂ eq.	1,86E+03	4,93E+01	3,83E+01	1,94E+03	8,45E+01	4,31E+00	5,36E+00	2,40E+01	5,00E-01	-4,68E+02
GWP-biogenic	kg CO ₂ eq.	1,36E+00	3,70E-02	1,37E-01	1,54E+00	1,47E-01	3,11E-02	2,77E-03	-3,12E-01	6,90E-05	4,24E+00
GWP-luluc	kg CO ₂ eq.	1,48E+00	2,91E-02	2,05E-02	1,53E+00	4,30E-02	3,88E-03	1,84E-03	3,40E-02	2,58E-04	9,83E-02
GWP-total	kg CO ₂ eq.	1,86E+03	4,93E+01	3,85E+01	1,95E+03	8,47E+01	4,35E+00	5,37E+00	2,38E+01	5,01E-01	-4,63E+02
ODP	kg CFC 11 eq.	1,20E-05	7,47E-07	3,73E-06	1,65E-05	1,61E-06	8,20E-08	1,08E-07	3,31E-07	1,45E-08	-7,67E-07
AP	mol H ⁺ eq.	8,53E+00	1,13E+00	7,75E-02	9,74E+00	3,47E-01	2,23E-02	1,73E-02	2,64E-01	3,54E-03	-1,37E+00
EP-freshwater	kg P eq.	5,00E-01	3,55E-03	4,91E-03	5,08E-01	9,49E-03	1,05E-03	3,65E-04	1,37E-02	4,15E-05	-2,02E-01
EP-marine	kg N eq.	1,84E+00	2,90E-01	2,70E-02	2,16E+00	1,21E-01	7,73E-03	5,88E-03	6,13E-02	1,35E-03	-3,52E-01
EP-terrestrial	mol N eq.	1,93E+01	3,21E+00	2,41E-01	2,28E+01	1,31E+00	8,28E-02	6,40E-02	6,90E-01	1,48E-02	-3,87E+00
POCP	kg NMVOC eq.	6,55E+00	8,89E-01	9,72E-02	7,54E+00	5,07E-01	2,83E-02	2,82E-02	2,07E-01	5,28E-03	-1,40E+00
ADP-minerals & metals *	kg Sb eq.	2,26E-03	7,18E-05	1,06E-04	2,44E-03	2,32E-04	2,10E-05	1,45E-05	1,48E-03	7,82E-07	5,70E-04
ADP-fossil*	MJ	1,91E+04	6,32E+02	2,22E+02	2,00E+04	1,22E+03	6,80E+01	7,77E+01	3,24E+02	1,23E+01	-3,89E+03
WDP	m ³	5,10E+02	2,40E+00	4,85E+00	5,17E+02	7,00E+00	4,77E-01	3,70E-01	4,03E+00	5,36E-01	-3,60E+01
Acronyms	GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption										

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

The negative value in module D indicates an environmental benefit.

Potential environmental impact – additional mandatory and voluntary indicators

Steel structural circular hollow sections

Results per functional or declared unit (1t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
GWP-GHG ¹	kg CO ₂ eq.	1,53E+03	3,09E+01	2,43E+01	1,58E+03	6,03E+01	4,32E+00	5,37E+00	2,38E+01	5,63E-01	-2,78E+02

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

Steel structural square and rectangular hollow sections

Results per functional or declared unit (1t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
GWP-GHG	kg CO ₂ eq.	1,85E+03	4,93E+01	3,83E+01	1,94E+03	8,46E+01	4,32E+00	5,37E+00	2,41E+01	5,01E-01	-4,67E+02

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

¹ The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.

Use of resources

Steel structural circular hollow sections

Results per functional or declared unit (1t)

Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
PERE	MJ	2,79E+03	9,59E+00	1,08E+01	2,81E+03	2,74E+01	6,16E+00	1,23E+00	5,21E+01	1,28E-01	1,40E+02
PERM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	2,79E+03	9,59E+00	1,08E+01	2,81E+03	2,74E+01	6,16E+00	1,23E+00	5,21E+01	1,28E-01	1,40E+02
PENRE	MJ	1,45E+04	4,00E+01	6,30E+01	1,46E+04	1,14E+02	1,89E+01	6,39E+00	1,03E+02	8,55E-01	-2,21E+03
PENRM	MJ.	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	1,45E+04	4,00E+01	6,30E+01	1,46E+04	1,14E+02	1,89E+01	6,39E+00	1,03E+02	8,55E-01	-2,21E+03
SM	kg	6,25E+02	0,00E+00	0,00E+00	6,25E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m ³	1,91E+01	5,90E-02	1,09E-01	1,92E+01	1,80E-01	2,45E-02	1,16E-02	1,57E-01	1,44E-02	-1,61E-01
Acronyms	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water										

Steel structural square and rectangular hollow sections

Results per functional or declared unit (1t)

Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
PERE	MJ	2,19E+03	1,57E+01	2,58E+01	2,23E+03	4,27E+01	6,16E+00	1,23E+00	5,27E+01	1,14E-01	2,36E+02
PERM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	MJ	2,19E+03	1,57E+01	2,58E+01	2,23E+03	4,27E+01	6,16E+00	1,23E+00	5,27E+01	1,14E-01	2,36E+02
PENRE	MJ	1,63E+04	6,49E+01	6,31E+01	1,65E+04	1,73E+02	1,89E+01	6,39E+00	1,04E+02	7,60E-01	-3,71E+03
PENRM	MJ.	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	MJ	1,63E+04	6,49E+01	6,31E+01	1,65E+04	1,73E+02	1,89E+01	6,39E+00	1,04E+02	7,60E-01	-3,71E+03
SM	kg	4,30E+02	0,00E+00	0,00E+00	4,30E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	m ³	1,78E+01	9,51E-02	1,46E-01	1,80E+01	2,68E-01	2,45E-02	1,16E-02	1,58E-01	1,28E-02	-2,71E-01
Acronyms	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water										

Waste production and output flows

Steel structural circular hollow sections

Waste production

Results per functional or declared unit (1t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
Hazardous waste disposed	kg	1,64E-01	2,11E-03	7,24E-03	1,73E-01	5,47E-03	3,62E-04	5,10E-04	1,96E-03	8,72E-05	-3,58E-02
Non-hazardous waste disposed	kg	3,02E+02	7,12E+00	6,28E+00	3,15E+02	6,50E+01	2,75E+00	6,64E+00	9,18E+02	9,00E+01	-3,05E+00
Radioactive waste disposed	kg	4,41E-02	2,02E-04	1,34E-04	4,45E-02	5,88E-04	1,54E-04	2,34E-05	6,14E-04	2,15E-06	5,08E-03

Output flows

Results per functional or declared unit (1t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Material for recycling	kg	3,90E+01	0,00E+00	4,68E+00	4,37E+01	0,00E+00	0,00E+00	0,00E+00	9,10E+02	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	2,51E-01	2,51E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy, electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy, thermal	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

Steel structural square and rectangular hollow sections

Waste production

Results per functional or declared unit (1t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
Hazardous waste disposed	kg	1,96E-01	3,34E-03	4,48E-03	2,04E-01	7,59E-03	3,62E-04	5,10E-04	1,98E-03	7,75E-05	-6,01E-02
Non-hazardous waste disposed	kg	2,32E+02	1,02E+01	6,22E+00	2,49E+02	8,79E+01	2,75E+00	6,64E+00	9,28E+02	8,00E+01	-5,13E+00
Radioactive waste disposed	kg	5,81E-02	3,33E-04	2,66E-04	5,87E-02	9,29E-04	1,54E-04	2,34E-05	6,20E-04	1,91E-06	8,54E-03

Output flows

Results per functional or declared unit (1t)											
Indicator	Unit	A1	A2	A3	Tot.A1-A3	A4	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Material for recycling	kg	5,36E+01	0,00E+00	4,68E+00	5,83E+01	0,00E+00	0,00E+00	0,00E+00	9,20E+02	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	2,52E-01	2,52E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy, electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy, thermal	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

Information on biogenic carbon content

Steel structural circular hollow sections and Steel structural square and rectangular hollow sections

Results per functional or declared unit		
BIOGENIC CARBON CONTENT	Unit	QUANTITY
Biogenic carbon content in product	kg C	0
Biogenic carbon content in packaging	kg C	0

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂.

Environmental additional information

The recycled content of the products is declared below, depending on whether the steel used comes from an EAF furnace or a blast furnace.

The calculation is based on certificates or supplier declarations of the recycled content.

Recycled content	From EAF %	From BOF %
Steel structural circular hollow sections	84%	14%
Steel structural square and rectangular hollow sections	84%	15%

Differences versus previous versions

Compared to 2022, for circular sections and square hollow products there is a slight increase in impacts due to:

- the increase in the use of Indian steel rather than European steel;
- to a slight decrease in the scrap content in the product

From a methodological point of view, it should be noted that:

- Various primary data have been collected from manufacturers, using their EPDs to improve data quality
- The database has been updated from Ecoinvent 3.9 to Ecoinvent 3.10; for some processes it led to a worsening of various impact categories

Phase A4 records a substantial decline thanks to the use of intermodal transport.

The database is updated to Ecoinvent 3.10

/

References

- General Programme Instructions of the International EPD® System. Version 3.01.
- PCR CONSTRUCTION PRODUCTS, PCR 2019:14, VERSION 1.1 del sistema EPD®
- EN 15804:2012+A2:2019 Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
- Studio LCA di tubi di acciaio elettrosaldati per il settore costruzioni: Tubi quadri rettangoli lavorati sia a freddo che a caldo, Tubi tondi lavorati sia a freddo che a caldo – aggiornamento dati 2023 del 14/10/2024 - e3 studio associato di consulenza www.ecubo.it
- EPD Acciaeria Arvedi Spa “Non-alloyed structural steels - Hot rolled coils, strips and sheets”, S-P-11471 - 30/11/2023

